

Richmond Plywood Corporation Limited

RICHFLOR™ **UNDERLAYMENT**



RICHFLOR™ UNDERLAYMENT is a premium grade Douglas-Fir intermediary layer of plywood typically installed on top of a subfloor to provide a solid base for the additional installation of hardwood or laminate flooring, carpet, ceramic tile, vinyl, or resilient flooring. RICHFLOR is a specially developed solid-face premium-core underlayment sanded to fine tolerances for a smooth and stable surface.

Solid Surface – constructed using higher-grade face veneers that are repaired using only wood putty and patches prior to sanding in order to provide a smooth, uniform solid surface free from open defects; touch-sanded surfaces for direct application of carpet and pad, and full-sanded surfaces for use under tile and resilient floor coverings.

Puncture Resistant – premium grade core veneers and minimal core gaps serve to resist dents and prevent punctures from point or concentrated loads.

Stability and Durability – bonded under high temperature and pressure with a waterproof phenol-formaldehyde resin adhesive, RICHFLOR Underlayment is a highly stable and durable panel.

NAUF – plywood manufactured by Richply contain No Added Urea Formaldehyde and are exempt from US HUD, CARB, and TSCA Title VI formaldehyde regulations.

Easy to Install – a factory applied nail guide is available that simplifies installation by identifying fastener positioning to ensure an even and properly secured floor.

50-Year Limited Warranty – when handled and installed in accordance with RICHFLOR Underlayment installation guidelines, Richply warrants against delamination, puncture, bleed-through, staining or discolouration of the floor coverings. For more warranty and installation details, go to www.richply.com.




Richmond Plywood Corporation Limited

13911 Vulcan Way, Richmond, B.C., Canada V6V 1K7

Tel: 604-278-5710 Fax: 604-278-2617 email: sales@richply.com

Quality Plywood Since 1956



Richmond Plywood Corporation Limited

RICHFLORTM **UNDERLAYMENT**

Handling Underlayment

Always protect RICHFLOR Underlayment against physical damage or water prior to application. Before installing, allow RICHFLOR panels to acclimatize for several days in the rooms where they will be installed by standing them on edge and separating them to permit air circulation.

Installing Underlayment

RICHFLOR Underlayment should only be installed on a clean, dry, structurally sound, level and securely fastened subfloor. Ensure the subfloor is thoroughly scraped, swept, vacuumed and free of construction dust and debris. Install RICHFLOR Underlayment smooth side up. For detailed RICHFLOR Underlayment installation guidelines, go to www.richply.com.

Environmentally Responsible

Richply is committed to sound environmental practices and complying with the laws and regulations for protecting our forests and ensuring the principles of forest certification. Richply is third party certified to internationally recognized and respected standards: 1) Programme for the Endorsement of Forest Certification (or PEFC); and 2) Forest Stewardship Council®. Independent third parties verify annually that Richply maintains Chain-of-Custody processes that meet these certification standards.

Panel Specifications:

RICHFLOR Underlayment is Made in Canada by Richply under quality assurance by APA – The Engineered Wood Association to meet or exceed CSA and PS-1 product standards.

RICHFLOR Underlayment is manufactured with grain direction of face/back veneers running parallel to the long edges of the panel. Standard dimensions are 1220mm x 2440mm (4'x8'). A factory applied nail guide is available in both 1220mm x 2440mm (4'x8') and 1220mm x 1220mm (4'x4') patterns. Other panel thicknesses may be available on special order.

Thickness	# of Plies	Surface Finish	Thickness Tolerance	kg (lbs) per Sheet
8.0mm (5/16")	3	Full-Sand	+/- 0.5mm (1/64 in)	14.9 (32.9)
8.5mm (11/32")	3 or 4	Touch-Sand	+/- 1.0mm (1/32 in)	15.2 (33.4)



Richmond Plywood Corporation Limited

13911 Vulcan Way, Richmond, B.C., Canada V6V 1K7

Tel: 604-278-5710 Fax: 604-278-2617 email: sales@richply.com

Quality Plywood Since 1956